

## 2.1 Home Theater with DVD



# CS-500

Sleek, simple and small, the CS-500 home theater system puts the ultimate cinema experience right into your living room with fewer wires and components. By applying Dolby® Virtual Speaker technology, this amazing little setup delivers the effect of a large, 5.1 home theater system with just two compact speakers, a subwoofer, and an A/V center.

Each magnetically shielded (so it won't interfere with your TV) speaker employs dual 2.5" high-output woofers and a 0.75" horn-loaded tweeter. Our Tractrix® Horn technology is what allows this system to deliver genuine, lifelike sound as well as produce more output using less energy.

The down-firing subwoofer utilizes a powerful 6.5" woofer. Due to its compact size, this heavy-hitter can easily be hidden away while still delivering dramatic low-end effects.

The A/V center features a built-in Class D amplifier that distributes 35 watts of power to each speaker and 100 watts of power to the subwoofer. It also includes a progressive scan DVD/CD player, AM/FM tuner, and three auxiliary inputs. The CS-500 even has the ability to pass high-definition signals through a component output and can simplify all of the auxiliary input connections into a single convenient output to the TV. A universal IR remote control directs all system functions as well as those of the TV and other entertainment devices.

Not only is it easier than buying separate audio components, the CS-500 can be up and running in as little as 10 minutes. All you have to do is connect the speakers, subwoofer and TV to the A/V center using the color-coded wiring and then plug in one power cord—it's that simple. Available in a black finish, the CS-500 also has a clean, modern design that fits comfortably into any living environment.

- Dolby® Virtual Speaker technology simulates 5-channel sound
- Progressive scan DVD/CD player, AM/FM tuner
- Three auxiliary inputs for games, MP3 players and other devices
- Universal IR remote controls entire system
- Speakers are wall mountable using 1/4" - 20 inserts (not included)
- Compact, wired subwoofer delivers dramatic low-end effects

### SPECIFICATIONS

frequency response	41Hz to 20kHz ± 3dB
amplifier power	Subwoofer: 100W continuous ≤10% THD+N Speakers: FTC rated 35 W/channel continuous, 2 channels driven, ≤1% THD+N
crossover frequency	175Hz, 24dB/Octave
maximum acoustic output	110dB
high frequency horn	MicroTractrix Horn
midrange	2.5" paper cone
subwoofer	6.5" downward firing
audio inputs	Digital: coax, optical Analog: line level
weight	37 lbs (16.78kg)
Front Dimensions (HxWxD)	8.6" x 4" x 5.5" (14.2 x 10.2 x 14cm)
Subwoofer Dimensions (HxWxD)	15" x 11" x 18" (38 x 27.9 x 45.7cm)
Component Dimensions (HxWxD)	3.5" x 15.5"W x 9.5" (8.9 x 39.4 x 24.1cm)
accessories	Included: controller, setup guide, owner's manual, remote, batteries, composite cable, audio cable, FM antenna, AM antenna, two 15' speaker cables, subwoofer cable, rubber pads, white gloves
features	USB, JPEG, MP3, Dolby Digital, DTS, FM/AM, Xvid, RDS
finishes	Controller: black plastic Satellites: high-gloss piano black plastic Subwoofer: black medium density fiberboard
voltage	120V
export voltage	230V

www.klipsch.com  
1-800-KLIPSCH

All specifications are subject to change without notice. ©2008

