

KC-25

ICON SERIES CENTER CHANNEL SPEAKER PERFECTLY MATCHES ALL ICON MAIN SPEAKERS

MINIMALIST, CONTEMPORARY DESIGN

Small but solid MDF Black Ash cabinet complements today's style of accompanying audio and video components in multiple room décors

TRACTRIX® HORN

Proprietary Klipsch technology with a refined 90° x 90° dispersion pattern expands the prime listening area to enhance the vocal clarity of your movies no matter how broad an area the audience is placed in the room

ALUMINUM DIAPHRAGM COMPRESSION DRIVER (TWEETER) WITH LINEAR TRAVEL SUSPENSION (LTS)

Combined with the Tractrix® Horn, the one-inch, solid-formed metallic, high-frequency diaphragm works in conjunction with a precise phasing plug at the horn throat to create a highly efficient driver with unmatched clarity and lack of distortion. The new Linear Travel Suspension assures the most precise diaphragm excursion, increasing high-frequency detail and smoothness.

INJECTION MOLDED GRAPHITE WOOFERS

Dual woofers with light, yet very stiff diaphragms matched with massive motor structures precisely reproduce, in conjunction with the horn-loaded LTS tweeter, distinct vocal clarity, a must for any center channel speaker, along with the realistic presentation of all other sounds assigned to this very important speaker used consistently in any Home Theater system

HIGH QUALITY, HIGH DEFINITION NETWORK

Increases overall speaker efficiency while reducing distortion

FLUSH-MOUNTED HORN FASCIA AND WOOFERS

Reduces front-baffle diffraction for precise imaging, increased dynamics and overall sound accuracy

5-WAY BINDING POSTS

Provide maximum connection flexibility

STRONG, FLEXIBLE, FULLY-REMOVABLE GRILL

Adds a rich look that is acoustically transparent



SPECIFICATIONS	KC-25
Frequency Response	82Hz-23KHz ± 3dB
Low Frequency Extension	74Hz
Power Handling	100W RMS / 400W Peak
Sensitivity	98dB @ 2.83V / 1m
Nominal Impedance	8 ohms compatible
Crossover Frequency	1800Hz
High Frequency Driver	1" (2.54cm) Aluminum diaphragm compression driver mated to 90° x 90° square Tractrix® Horn
Low Frequency Drivers	Dual 5.25" (13.3cm), magnetically shielded IMG woofers
Inputs	Single binding posts
Enclosure Material	MDF (medium density fiberboard)
Enclosure Type	Sealed
Height	7.25" (19.2cm)
Width	18.75" (50.3cm)
Depth	7.25" (16.4cm)
Weight	16lbs (7.3kg)
Finish	Black Ash vinyl
Built From	2011