

## Behind-the-Screen Cinema System



**THX**

Once movie-goers experience the unbridled dynamics and intense realism of the KPT-535-T, they will have a new favorite theater for life. This THX®-Certified high-performance screen and stage loudspeaker system, with its 24-inch depth, allows for more real estate where it matters – in the auditorium.

Embracing the concept of a three-way system, with direct radiated bass cabinet in a behind-the-screen application, the KPT-535-T utilizes the KPT-904-LF double, 15-inch low-frequency system.

Reproducing the critical dialogue range is the KPT-402-MF mid-bass Tractrix® Horn coupled to the Klipsch K-1133 two-inch exit titanium compression driver. The high frequencies are easily handled by the KPT-Grand-HF-T Tractrix Horn. This advanced Tractrix Horn geometry and compression driver technology creates a large soundstage with well-defined imaging, resulting in a more genuine, lifelike sound.


This system is also available with a mid/high passive crossover for a bi-amp configuration and is known as the KPT-535-N.

# KPT-535-T

## SPECIFICATIONS

FREQUENCY RESPONSE*	45Hz-19kHz $\pm$ 3dB, -10dB @ 32Hz
POWER HANDLING	900 watts
CROSSOVER POINTS	400Hz, 2kHz
DELAY	LF- 0.7ms MF- 0ms HF- 1.1ms
CROSSOVER SLOPE	24dB/Octave
SENSITIVITY	104dB
COVERAGE	HORIZONTAL $90^{\circ} \pm 20^{\circ}$ 250Hz-16kHz VERTICAL $60^{\circ} \pm 20^{\circ}$ 450Hz-16KHz
SYSTEM COMPONENTS	LF - KPT-904-LF - 400 watts/ woofer MF - KPT-402-MF - 50 watts HF - KPT-GRAND HF-T - 50 watts
HEIGHT	81" (206cm)
WIDTH	40.25" (102.2cm)
DEPTH	23.25" (59.1cm)
WEIGHT	215 lbs. (97.6kg)

\*Frequency response behind a screen with horn equalization applied



www.klipsch.com  
1-800-KLIPSCH