



THX

KPT-535-4-T

SPECIFICATIONS

With its high efficiency, low distortion, controlled directivity and flat frequency response, the THX®-Certified KPT-535-4-T behind-the-screen system delivers the unbridled dynamics and intense realism required for today's most exciting soundtracks.


An enhanced version of Klipsch's KPT-535-T, this system features a KPT-415-LF quad 15-inch direct-radiating bass unit for greater output in large auditoriums. Yet it retains the smaller system's 24-inch depth, minimizing the valuable theater space consumed by the area behind the screen.

The dialogue range is superbly handled by a KPT-402-MF Tractrix® Horn fronting a K-1133 two-inch exit titanium compression driver. And, a KPT-Grand-HF-T Tractrix Horn ensures smooth, effortless treble reproduction. This advanced Tractrix Horn geometry and compression driver technology creates a large soundstage with well-defined imaging, resulting in a more genuine, lifelike sound.

This is also available with or without a mid/high passive crossover for a bi-amp configuration and is known as the KPT-535-4-N.

FREQUENCY RESPONSE*	43Hz-19kHz \pm 3dB, -10dB @ 26Hz
POWER HANDLING	1700 watts
CROSSOVER POINTS	400Hz, 2kHz
DELAY	LF- 0.6ms MF- 0ms HF- 1.1ms
CROSSOVER SLOPE	24dB/Octave
SENSITIVITY	107dB
COVERAGE	HORIZONTAL $90^{\circ} \pm 30^{\circ}$ 200Hz-16kHz VERTICAL $60^{\circ} \pm 30^{\circ}$ 300Hz-16kHz
SYSTEM COMPONENTS	LF - KPT-415-LF - 800 watts/woofer pair MF - KPT-402-MF - 50 watts HF - KPT-GRAND HF-T - 50 watts
HEIGHT	86" (218cm)
WIDTH	39.75" (101cm)
DEPTH	23.75" (60cm)
WEIGHT	280 lbs. (127.1kg)

*Frequency response behind a screen with horn equalization applied



www.klipsch.com
1-800-KLIPSCH