



KPT-684

The Klipsch KPT-684 is a high-quality THX[®]-Approved cinema subwoofer that features an advanced low-frequency driver design inside a bass-reflex enclosure for smooth response to the lowest audible frequencies.

The system utilizes dual 18-inch drivers that gain the system's amazing 105dB sensitivity through the use of large, geometrically optimized magnet structures and lightweight cones.

Built from the inside out for performance and durability, the KPT-684 packs a punch that lets audiences hear as well as feel the impact of edge-of-your-seat entertainment.

SPECIFICATIONS


FREQUENCY RESPONSE ¹	36Hz-800Hz \pm 3dB, 25 Hz - 2.2k Hz -10dB
POWER HANDLING ²	600 watts (65V) 25Hz - 250Hz
RECOMMENDED AMP. POWER	600 watts continuous / 2400 watts peak
CALC. MAX. CONT. OUTPUT ³	132dB
SENSITIVITY ⁴	105dB
NOMINAL IMPEDANCE	8 ohms (3.6 min. @ 22Hz) woofers wired in parallel
TRANSDUCERS	Two K-47-EP2 18" woofers
INPUT CONNECTORS	Barrier strip
HEIGHT	48.75" (123.8cm)
WIDTH	23.5" (59.7cm)
DEPTH	30.5" (77.5cm)
WEIGHT	155 lbs. (70kg)

¹ 3M, Half-space anechoic

² AES Standard, continuous pink noise, 6dB peaks.

³ Calculated at 1M half-spaced at power handling power input, woofers wired in parallel.

⁴ SPL at 1M, half spaced anechoic with 2.83 volts input, woofers wired in parallel.



www.klipsch.com
1-800-KLIPSCH