



KPT-904-B

SPECIFICATIONS


FREQUENCY RESPONSE*	45Hz-19kHz \pm 3dB, -10dB @ 32Hz
POWER HANDLING	850 watts
CROSSOVER POINTS	800Hz
DELAY	LF- 0ms HF- 0.1ms
CROSSOVER SLOPE	24dB/Octave
SENSITIVITY	104dB
COVERAGE	HORIZONTAL $90^{\circ} \pm 20^{\circ}$ 250Hz-14kHz VERTICAL $60^{\circ} \pm 20^{\circ}$ 2kHz-19kHz
SYSTEM COMPONENTS	LF - KPT-904-LF - 400 watts/ woofer HF - KPT-904-HF - 50 watts
HEIGHT	55.5" (141cm)
WIDTH	27.25" (69.2cm)
DEPTH	17.75" (45.1cm)
WEIGHT	156 lbs. (71kg)

*Frequency response behind a screen with horn equalization applied

Once movie-goers experience the unbridled dynamics and intense realism of the KPT-904-B, they will have a new favorite theater for life. A mid-sized screen and stage loudspeaker system, it is especially suited for stadium seating.

The higher frequencies are handled by the KPT-904-HF, which is mated to the KDE-75-8P, 3" titanium diaphragm compression driver on a K-510 horn. This advanced Tractrix® Horn geometry and compression driver technology creates a large soundstage with well-defined imaging, resulting in a more genuine, lifelike sound. The bass punch is provided by the KPT-904-LF dual, 15-inch, low-frequency cabinet.

The bi-amped KPT-904-B delivers sensational performance and accurate coverage control, all at a remarkable price. It is available with a passive crossover for mono-amp operation as the KPT-904-M.



www.klipsch.com
1-800-KLIPSCH