

PRO-6602-W



SILK DOME TWEETERS

The silk dome high frequency driver of the 6000 series offers all of the benefits of the titanium counterparts of the 4000 series with a noticeably smoother, more balanced reproduction, particularly in the upper vocal range of 2kHz - 8kHz. This results in a warm, natural, and lifelike sound while still displaying the exceptional dynamics and power inherent in a Klipsch speaker.

HONEYCOMB FIBERGLASS WOOFERS

The honeycomb fiberglass woofers of the 6000 series offer an extension of the woven construction - exceptionally low distortion and breakup characteristics while offering superior efficiency over heavier, more traditional cone materials - while offering superior linearity and damping characteristics for warm, balanced, natural low frequency reproduction.

CONTROLLED DISPERSION TECHNOLOGY® (CDT)

Klipsch's CDT technology allows for easy and expansive positioning of high frequency and mid frequency drivers, allowing for aimable, on-axis response from an architectural speaker.

ADJUSTABLE TWEETER AND IMPEDANCE SWITCHES

Featuring a 2-position impedance switch and a 3-position tweeter level adjustment enables you to match your musical preferences and system requirements.

EDGE-TO-EDGE GRILL

Covering the whole of the speaker makes painting the product both simpler and quicker. Premium Neodymium magnets make it easy to install and remove and ensure a secure and flush fit without any moving parts. The flat grill allows better harmonization with today's modern interior designs and disappear into the background, enabling sound to take center stage.

SEAMLESS HIGH PERFORMANCE

The Klipsch Professional Series introduces a new line of high-performance architectural speakers unlike any you've heard before. Superior acoustic technology makes the Professional Series the most dynamic, powerful, direct-radiating speakers available.

SPECIFICATIONS

SYSTEM	3-way In-wall
FREQUENCY RESPONSE	55Hz - 22kHz
POWER HANDLING (Cont/Peak)	80W/160W
IMPEDANCE	4 - 8 Ohms switchable
HIGH FREQUENCY DRIVER	1" Silk Dome Tweeter
MIDRANGE	1.5" Silk Dome Driver
LOW FREQUENCY DRIVER	Two 6.5" Honeycomb Fiberglass Woofers
HOLE DIMENSION	20.9"(530mm) H x 7.9"(200mm) W x 3.8"(97mm) D
DIMENSIONS	22.1"(562mm) H x 9.1"(232mm) W x 4.2"(107mm) D
BACK BOX SIZE	1340 in ³
WEIGHT	7.7 lbs (3.5kg)
FINISH	White (paintable)