

6.5" Two-Way Square In-Ceiling Loudspeaker



R-2650-C2

Adding to Klipsch's extensive lineup of architectural products, the contemporary-designed R-2650-C2 square in-ceiling speaker gives installers yet another high-performance, flush-mount option to choose from. Perfect for home theater or stereo music applications, this discrete audio solution delivers powerful and detailed sound.

Featuring the same drive components as its round counterpart, the two-way R-2650-C2 employs a 6.5-inch gray polymer woofer cone and a 1-inch soft/silk dome tweeter for superior depth and clarity.

Available in a white finish, the R-2650-C2 is paintable and can be paired with the Klipsch IK-650-C2 installation kit (sold separately). This kit design incorporates a mud ring, breakaway tie and color-coded brackets for easy speaker size identification. It also includes perforated metal wings that easily fasten to studs via screws, staples or nails. Painted white for easy marking and placement, these metal wings can be folded around the edge of the studs if necessary.

By adding the affordable R-2650-C2 to its high-end, easy-to-install architectural series, Klipsch proves it now has a speaker for every application and lifestyle.

- Weatherized components
- Rugged ABS frame
- Treble attention switch
- Paintable to match ceiling

SPECIFICATIONS

FREQUENCY RESPONSE	77Hz-20kHz \pm 3dB
SENSITIVITY	91dB @ 1 watt/1 meter
NOMINAL IMPEDANCE	8 ohms
CROSSOVER FREQUENCY	2300Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	ABS/ Infinite baffle, front flush with ceiling
DRIVE COMPONENTS	Two-way system using one 1"(2.5cm) silk dome compression tweeter and one 6.5" (16.5cm) poly woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	4.1 lbs. (1.9kg)
HEIGHT x WIDTH	9.3" (23.6cm) x 9.3" (23.6cm)
MOUNTING DEPTH	4.8" (12.2cm)
CUTOUT DIMENSIONS	8.1" (20.6cm) x 8.1" (20.6cm)
INSTALLATION KIT	IK-650-C2 (sold separately)
FIRE RATED ENCLOSURE	N/A

www.klipsch.com
1-800-KLIPSCH

