

## R-2650-CSM II



### DUAL TWEETER/DUAL VOICE COIL SPECIAL APPLICATION SPEAKER WITH A NEW LOW PROFILE LOOK

The Klipsch R-2650-C II, with stereo sound from a single speaker, is the perfect sound solution for smaller areas that can only accommodate one physical speaker (bathrooms, laundry rooms, walk-in closets, etc.), or areas where a stereo speaker pair is not practical (such as hallways). The R-2650-C II maintains the core technology use of high-quality, dual 1" Silk Dome tweeters combined with a 6.5" Polypropylene woofer in a 2-way design. Now with a new low-profile, more elegant grille it continues as an excellent choice for everything from whole house audio to surround sound use.

### NEW SLIMTRIM™ GRILLE

With an all new grille, the visible frame size is reduced by 90% and grille depth is reduced by 80% over the previous design, for a more edge-to-edge consistent look that blends in with the wall more attractively. The new aluminum, paintable, magnetic grille attaches tightly and securely with ease to virtually eliminate resonant distortion.

### DUAL SILK DOME TWEETERS

The low-resonance, .75" Silk Dome tweeters reproduce high frequencies from both channels of a stereo source with ambience.

### DUAL VOICE COIL POLYPROPYLENE WOOFER

The dense, yet lightweight, polymer cone utilizes one voice coil for each channel of a stereo source in order that all low frequency information from both channels is heard.

### SURE-GRIP MOUNTING DOGS

Provide even pressure against drywall for long-term installation reliability.

### COMPATIBLE WITH THE KLIPSCH IK-650-C INSTALL KIT

For increased mounting flexibility and pre-install marking during new construction.

### COMPATIBLE WITH THE KLIPSCH ME-650-C FIRE-RATED SPEAKER ENCLOSURE

For meeting building codes and/or reduction of transferred sound between rooms.

SPECIFICATIONS	R-2650-CSM II
Frequency Response	75Hz-20KHz ± 3dB
Sensitivity	94dB @ 2.83V / 1m (both channels driven)
Nominal Impedance	8 ohms compatible
Crossover Frequency	3000Hz
Power Handling	50W RMS / 200W Peak
Recommended Amplifier Power	100 W
High Frequency Driver	Dual .75" (1.91cm) Silk dome tweeters
Low Frequency Driver	6.5" (16.51cm) Polypropylene cone dual voicecoil woofer
Enclosure Material/Type	ABS/Infinite baffle, front flush with wall
Wire Gauge Accommodated	12 ga
Dimensions	9.5" (24.13cm)
Cutout Dimensions	8.25" (20.96cm)
Mounting Depth	4.2" (10.67cm)
Weight	7.2 lbs. (3.25kg)
Finish	White paintable frame and grille
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)
Built From	2012