



## Dual 8" Two-Way Floorstanding Loudspeaker

# RF-5

Designed to the same standards as our flagship RF-7, the RF-5's sonic clarity and impact, from top to bottom, place it in the very top echelon of high-performance loudspeakers. And it is so amazingly efficient that it demands only about one-eighth the amplifier power of conventional speakers. Whether standing alone in a high-end stereo music system or anchoring a powerhouse home theater, the RF-5 brings the experience home with maximum intensity.

The RF-5's tweeter is a 1-inch titanium dome compression driver with an uncommonly large 9.6-ounce magnet. It is loaded by an 8-inch square 90° x 60° Tractrix® Horn, which raises the driver's efficiency and controls its radiation pattern to minimize detail-blurring reflections from walls, floor, and ceiling. The dual 8-inch woofers have stiff, lightweight Cerametallic™ cones, rigid, low-resonance cast-polymer frames, enabling them to generate staggering levels of bass without strain or distortion. All drivers are magnetically shielded to prevent interference with direct-view television sets.

Amplifier connections are via two pairs of binding posts, which are linked with jumpers for normal wiring. Removing the jumpers allows the speaker to be bi-wired. The speaker's "floating" grille minimizes diffraction, and its feet can be fitted with rubber pads or spikes. The rear-ported cabinet is available finished in Medium Cherry, Blonde Maple, or Black Ash wood veneer.

- Extremely high sensitivity, power handling, and output capability
- Tractrix Horn titanium dome compression driver tweeter for clean, detailed highs
- Cerametallic cone woofers with cast-polymer frames
- Bi-wire compatible inputs
- Magnetically shielded to prevent video interference
- Real wood veneer finishes

### SPECIFICATIONS

BANDWIDTH	34Hz-20kHz ± 3dB
SENSITIVITY	99dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2500Hz
POWER HANDLING	150 watts (600 watts peak)
ENCLOSURE TYPE	Bass-reflex via rear-firing port
DRIVE COMPONENTS	Two way system using one 1" (2.5cm) magnetically shielded, titanium diaphragm compression driver with an 8" (20.3cm) square 90° x 60° Tractrix horn and two 8" (20.3cm) magnetically shielded, Cerametallic cone woofers
WEIGHT	62 lbs. (28.2kg)
HEIGHT	42.3" (107.4cm) w/feet, 41.4" w/o feet
WIDTH	9" (22.9cm)
DEPTH	16.4" (41.7cm) w/grille, 14.5" w/o grille
FINISH	Black Ash or Medium Cherry wood veneer



www.klipsch.com  
1-800-KLIPSCH