

## 6.5" Two-Way In-Wall Loudspeaker



# SCW-2

Klipsch Custom Series architectural speakers are carefully engineered using the latest materials and technology to deliver superb performance and unparalleled value. A medium-size in-wall, the versatile, easy-to-install SCW-2 is an excellent choice for distributed-music systems and other applications requiring unobtrusive, high-quality loudspeakers with high output capability. SCW-2s can work well as surround speakers in home theater systems, for example, or for all channels if a subwoofer is included. And because they share so many design elements with our freestanding speakers, their sound blends perfectly in mixed systems, giving you maximum flexibility.

Constructed on a rigid, low-resonance cast-polymer frame, the SCW-2 delivers robust bass from its 6.5-inch IMG-cone woofer. A 1-inch aluminum-dome compression driver tweeter is mated to a 6-inch square 90° x 60° Klipsch Tractrix® Horn that can be pivoted to focus sound where needed — a significant benefit when circumstances dictate a less-than-ideal install location. A tweeter attenuation switch conveniently placed behind the grille provides another tool for tailoring the speaker's output to the acoustics of its environment.

The SCW-2's white frame and rustproof, powder-coated aluminum grille can be painted to match the wall; an IR punchout accepts standard infrared receivers. High-quality components and superior construction assure long, reliable service. And the speaker's 8-ohm impedance is compatible with all amplifiers.

- High sensitivity and power handling
- Durable cast-polymer frame with shallow 3.6" mounting depth
- Pivoting Tractrix Horn compression driver tweeter for clear sound in any location
- Tweeter attenuation switch and IR receiver punchout
- Frame and rustproof aluminum grille paintable to match wall

## SPECIFICATIONS

BANDWIDTH	42Hz-20kHz ± 3dB
SENSITIVITY	92dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2100Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	Infinite baffle system
DRIVE COMPONENTS	Two-way system using one 1" (2.5cm) aluminum dome compression driver tweeter with a pivoting 90° x 60° Tractrix Horn and one 6.5" (16.5cm) IMG cone woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	5 lbs. (2.3kg)
HEIGHT	14.1" (35.8cm)
WIDTH	9.1" (23.1cm)
MOUNTING DEPTH	3.6" (9.1cm)
CUTOUT DIMENSIONS	13" (33cm) x 8" (20.3cm)
FINISH	White
INSTALLATION KIT	W-650-IK



www.klipsch.com  
1-800-KLIPSCH