

The Klipsch C O R N W A L L speaker system

Klipsch CORNWALL speaker systems are designed as full-range speakers for either corner or wall placement. They are suitable for use in any or all the 3-positions for 3-channel stereo, or in combination with any other Klipsch speakers.

Recognizing that all speaker systems are best operated in a corner, the CORNWALL series are designed to give optimum performance in a corner, but to sacrifice as little performance as possible when operated against a wall. In the corner, bass response extends effectively to 35 cycles. The 15 inch bass drive unit (same as used in the KLIPSCHORN) assures a large direct radiating area. Additional radiation from the back-loading affords extended bass and high output at low diaphragm excursions and velocities. The result is extremely low distortion, of both amplitude and frequency modulation. The midrange and tweeter, also, use the same drive units as the KLIPSCHORN, so the middle and upper response are likewise smooth and distortion free.

Compatibility for stereo use with other Klipsch speakers has been accomplished through special application of the principles used in the balancing networks of other Klipsch systems. Response within a wide operating range has been adjusted to resemble that of the KLIPSCHORN.

The CORNWALL system was specifically balanced for and is offered as standard with the fifteen inch CW-ORTHO-15 drive system. However, for economy application the CORNWALL may be obtained with the CW-ORTHO-12 drive system or with the single 12" extended range driver. This can be upgraded to the balanced 3-way system.

Horizontal and vertical models are identical in structure, but due to height of tweeter and proximity of bass driver to walls, the vertical model will exhibit superior overall performance, especially in a corner.

KLIPSCH and ASSOCIATES, Inc

Hope

Arkansas

1

MARCH

1960

*we started including
the 2 specs with
all general literature
at P.A.K.'s command
on 26 Feb 60.*