

# Home Theater System



# QUINTET III

For over a decade, our Quintet™ home theater system has been an all-time best-selling product for us. Now in its third generation, this surround sound package still proves that compact dimensions and sophisticated style can coexist with dynamic sound.

Comprised of four miniature speakers and a low-profile center channel, the Quintet III home theater system incorporates decades of class-leading research and development experience. In fact, it applies the same cutting-edge technology that's found in our professional cinema products.

Each magnetically shielded satellite employs a 0.75-inch aluminum diaphragm tweeter coupled to an exclusive MicroTractrix Horn for precise high frequencies. The 3.5-inch long-throw woofers produce remarkable detail and clarity. The swiveling pedestal base featured on each satellite facilitates easy wall or shelf placement and gives the speaker a 180-degree range of motion, allowing users to widen or constrict the soundstage based on audience size.

The two-way magnetically shielded center channel uses the same MicroTractrix Horn tweeter and two of the 3.5-inch woofers found in the satellites to ensure an ideal sonic match and proper driver transition across the listening area.

In order to create the low-frequency power you can hear and feel, we recommend pairing the Quintet III Home Theater System up with our Sub-10 subwoofer (sold separately). The Sub-10 reaches deeper and hits harder thanks to a 10-inch, down-firing driver coupled to a highly efficient BASH amplifier.

In addition to its high-end components, the Quintet III home theater system has a modern, refined industrial design. While the satellites and center channel feature a dark gray finish with medium gray accents, the optional Sub-10 is available in a black ash vinyl finish with titanium accents.

- Five-channel surround sound package
- Horn-loaded tweeters maximize live qualities of music and movies
- High-output woofers deliver room-filling bass
- Clean, modern design fits any living environment
- Recommended Sub-10 subwoofer sold separately

## SPECIFICATIONS

FREQUENCY RESPONSE	Satellite: 120Hz-23kHz Center: 125Hz-23kHz
POWER HANDLING	Satellite: 50 watts (200 watts peak) Center: 75 watts (300 watts peak)
SENSITIVITY	Satellite: 91dB@2.83 volts/1 meter Center: 94dB@2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	Satellite: 2800Hz Center: 2700Hz
TWEETER	One .75" (1.9 cm) neodymium magnet compression driver
HIGH FREQUENCY HORN	90(d) x 40(d) Tractrix Horn
MIDRANGE	One 3.5" (8.9 cm) magnetically shielded woofer
ENCLOSURE TYPE	Bass-reflex via rear-firing port
DIMENSIONS	Satellite: 8.3" (21.1 cm) H x 5" (12.7cm) W x 6.3" (16cm) D Center: 5" (12.7cm) H x 12" (30.5cm) W x 6" (15.2cm) D
MOUNTING	Satellite: Base swivels for on-wall mounting via keyholes Center: Threaded insert
WEIGHT	Satellite: 3.5 lbs (1.6 kg) Center: 5.5 lbs (2.5 kg)

